

Product Specification Report

5-1200-Rev.00/2-13



Lubricates and protects against corrosion.

SLIDEZE HT

Hot bitumen lubricant

FEATURES/BENEFITS:

Lubricates	Prevents bitumen build-up during the manufacture of hot bitumen.
Protects	Provides long-term lubrication and protection even under extreme heat conditions.
Long lasting	Not water soluble and therefore cannot readily be washed away. Offers superior performance and does not require constant re-application.
Safer	Non-flammable and non-corrosive.
Easy to Use	Simply brush or spray a thin film over the hard surface.

USE:

Simply brush or spray a thin film over the hard surface.

APPLICATIONS:

Can be used anywhere lubrication and protection is required during the manufacture and loading of hot bitumen.

PRECAUTIONS:

For further information see MSDS.

SPECIFICATIONS:

Form.....	Liquid
Colour.....	Pale yellow
Odour.....	Nondescript
Melting point.....	Approximately -42°C
Boiling point.....	Greater than 250°C
Flash point.....	Approximately 178°C
Density (20 °C).....	0.9 g/cm ³
Miscibility in water.....	Insoluble
pH (20°C).....	Not applicable

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.